































## LF1200 Performance

Deflector	Nozzle	Stream Height (cm)	Flow Rate at Standard Pressures (l/h) Throw Radius at Standard Pressure (meter)			
			2.1 bar	2.4 bar	2.8 bar	3.1 bar
6 Degree Dark Purple 	Orange 44 Drill 	35-50	266 6.9	286 6.9	307 7.5	325 7.5
	Purple 3/32" 	35-53	316 7.2	341 7.2	366 7.8	388 7.8
	Yellow 38 Drill 	40-53	370 7.5	402 7.5	429 8.1	454 8.1
12 Degree Blue 	Orange 44 Drill 	71-99	266 8.1	286 8.4	307 8.7	325 8.7
	Purple 3/32" 	71-101	316 8.7	341 9.0	366 9.3	388 9.3
	Yellow 38 Drill 	76-109	370 9.0	402 9.6	429 9.6	454 9.6
17 Degree Sky Blue 	Orange 44 Drill 	124-152	266 9.3	286 9.9	307 10.2	325 10.2
	Purple 3/32" 	106-154	316 9.9	341 10.2	366 10.5	388 10.8
	Yellow 38 Drill 	109-154	370 10.2	402 10.5	429 10.8	454 10.8
21 Degree Olive Green 	Orange 44 Drill 	152-187	266 10.2	286 10.2	307 10.2	325 10.5
	Purple 3/32" 	127-190	316 10.2	341 10.5	366 10.5	388 10.5
	Yellow 38 Drill 	134-182	370 10.5	402 10.8	429 10.8	454 10.8

## LF2400 Performance

Deflector	Nozzle	Stream Height (cm)	Flow Rate at Standard Pressures (l/h) Throw Radius at Standard Pressure (meter)			
			2.1 bar	2.4 bar	2.8 bar	3.1 bar
10 Degree Lime 	Tan 30 Drill 	60-96	493 9.0	534 9.6	575 9.9	606 10.2
	Red 1/8" 	60-104	568 9.6	613 9.9	656 10.2	697 10.5
	Silver 9/64" Drill 	81-111	743 10.2	802 10.5	858 10.8	913 11.1
15 Degree Tangerine 	Tan 30 Drill 	71-127	493 9.9	534 10.2	575 10.8	606 10.8
	Red 1/8" 	88-137	568 10.2	613 10.5	656 11.1	697 11.1
	Silver 9/64" Drill 	106-144	743 10.8	802 11.1	858 11.7	913 11.7
22 Degree Dark Green 	Green 7/64" 	160-241	420 11.4	454 11.4	488 11.4	518 11.7
	Tan 30 Drill 	162-246	493 11.4	534 11.7	575 12.0	606 12.3
	Red 1/8" 	170-254	568 11.7	613 12.0	656 12.3	697 12.3
	Black 29 Drill 	287-304	636 12.3	688 12.6	738 12.6	784 12.9
	Silver 9/64" Drill 	182-259	743 12.0	802 12.9	858 13.2	913 13.5

For complete performance charts, please consult [www.rainbird.eu](http://www.rainbird.eu)