

ESP-9V SERIES

Battery-Operated Irrigation Controller



Plays Rough. Works Easy.

No AC Power? No problem. The ESP-9V Series Battery-Operated Controller combines intuitive programming with a rugged design to ensure you get reliable automatic irrigation control, even in harsh or humid conditions. The ESP-9V can truly be installed anywhere, making it the clear choice for a clear view forward.

Unmatched Warranty

Rest easy knowing your controller is backed by an industry-leading 5-year warranty.

Weatherproof

Designed with multilayer protection and IP-rated components, the ESP-9V can stand up to the elements.

Long Lasting

Get at least two year battery life when you use two 9-volt alkaline batteries or a minimum of one year with one 9-volt alkaline battery.

Intuitive

Easily program your control with a user-friendly interface that lets you choose the start times, watering options, and cycles that work for you.

Controller Features

- At-a-glance programming eliminates confusion by showing the run-time, start times and watering days for each zone.
- Large LCD display with easy to navigate user interface.
- Sensor input with bypass override.
- Master valve/pump-start circuit (multi-zone units only).
- Non-volatile (100-year) program memory.
- IP68 certified for protection against dust and water intrusion.
- The plastic controller case has outstanding resistance to weather, yellowing and aging.

Scheduling Features

- Dedicated manual watering button for easy operation.
- Automatic zone-stacking ensures that only one valve irrigates at a time. If zones are scheduled to water at the same time and date, the ESP-9V will automatically irrigate the lower number zone first.
- Contractor Rapid Programming™ automatically copies the start times and watering days from zone 1 to all remaining zones at initial setup.

- Run times, start times and watering days are customizable by zone.
- 6 independent start times per zone.
- 4 watering day options per zone: Custom days of week, Cyclic (every 1 to 30 days) and ODD calendar days and EVEN calendar days.
- Delay watering (1 to 9 days).

Advanced Features

- Contractor Default™ save/restore.
- Rain Sensor bypass for all zones.
- Manually water ALL zones or SINGLE zone on demand.
- One-touch manual start.

Certifications

- cULus, FCC, IC, CE, RCM (AMCA), IP68, RoHS

Controller Dimensions

Width: 5.35" (13,59 cm)
Height: 4.04" (10,26 cm)
Depth: 2.42" (6,15 cm)
Weight: 2 lbs (907 g)

LCD Screen Size

Width: 2.25" (5,72 cm)
Height: 1.25" (3,18 cm)

How to specify your model:

ESP9V1 1-Zone ESP-9V Controller
ESP9V2 2-Zone ESP-9V Controller

ESP9V6 6-Zone ESP-9V Controller
ESP9V1SOL 1-Zone + 9V Solenoid
ESP9VDVKIT 1-Zone + 1" DVF Valve (NPT)

ESP-9V SERIES



Specifications

The controller shall be the type which may be installed in a valve box underground. The controller shall function normally if submerged in water.

The irrigation controller shall be housed in an ASA plastic enclosure. The battery compartment shall be dual-sealed to prevent water from entering the compartment. The controller shall have two mounting slots for screws allowing the controller to be securely mounted inside a valve box.

The controller shall be designed to operate for one full year in normal conditions using one 9-volt alkaline battery or two years with two 9-volt batteries.

The controller shall operate (depending on model) 1, 2, or 6 zones.

2 and 6 station models shall support a master valve.

6 station models shall include a second common wire to aid during installation.

All valves shall use the Master Valve.

One sensor input shall be present on the controller and shall accommodate a dry contact rain sensor.

The controller shall allow the user to obey/ ignore the rain sensor inputs for all zones.

The controller shall have station run time capability from 1 to 240 minutes in one minute increments, a 365-day calendar with leap year and up to six start times per zone.

Each zone shall be capable of being set to any of the following day schedules: custom, cyclic (every 1 to 30 days), odd-31 calendar days, and even calendar days.

The controller shall have a global seasonal adjust feature, adjustable from 10% to 200% in 10% increments. (The maximum resulting run time per zone will be 399 minutes.)

A Delay Watering feature shall allow the user to suspend irrigation from 1 to 9 days.

The controller shall have a dedicated manual watering button to initiate watering for all zones or specific zones for the programmed duration.

The controller shall be capable of manually starting/stopping single valve or all valves for a specified time.

The controller shall be capable of manually starting/stopping single valve or all valves for the programmed run times



Rain Bird Corporation
6991 East Southpoint Road
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Technical Services
(800) RAINBIRD (1-800-724-6247)
(U.S. and Canada)

Rain Bird Corporation
970 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

Specification Hotline
1-800-458-3005 (U.S. and Canada)

Rain Bird International, Inc.
1000 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 963-9311
Fax: (626) 852-7343

The Intelligent Use of WaterSM