



Rain Bird PSRP Pump Start Relay U-110 volt

CATALOG NUMBER

RBLC24WG1

WIRING DIAGRAM

RBLC24WG10412

DATE CODE

ENCLOSURE RATING

Nema Type: 3R

PHASE

SINGLE

HERTZ

Sixty (60)

LARGEST MOTOR

2

ELECTRICAL RATING

110 v 31 FLA

SHORT CIRCUIT RATING

110 v 5kA

RAIN BIRD

If you have any questions about this product, please visit: www.rainbird.com or call: 1 800-724-6247

Use copper wire rated at 75 Deg. Celcius only - - - Disconnect supplied by others.
NOTE: all motors must be thermally protected. Circuit protection must be provided by installer.
Grounding per N.E.C.- Ground lug torque: 45 in/lb. Terminal block torque specs: 9m/lb.

THIS PRINT IS THE PROPERTY OF RAINBIRD CORPORATION, AND IT EMBODIES A PROPRIETARY DESIGN WHICH SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES UNLESS SPECIFIC WRITTEN AUTHORIZATION BY RAINBIRD CORPORATION IS GIVEN. THIS PRINT IS LOANED, SUBJECT TO RETURN UPON DEMAND.

© 2012 Munro Companies INC all rights reserved.