



32SA POP-UP GEAR DRIVEN ROTOR

“SA” for Simple Adjust

*Replaces
competitive
product such as
Orbit® Saturn III™*

SPRAYS 19 TO 32 FEET

ADJUST FROM 40-360°

READY FOR INSTALLATION

1/2" INLET



Simple to use:

Find your fixed LEFT edge.

Using the palm of your hand, turn the center cap to the right until it stops. Then turn it to the left until it stops. This is your fixed left edge. Arc is preset to rotate 180°.

Adjusting the Pattern.

Using a screwdriver, adjust the arc dial clockwise (+) to increase the arc or counterclockwise (-) to decrease the arc. Pattern is adjustable from 40° to 360°. Do not turn past right or left stop. Adjust wet or dry.

Adjusting the Radius.

Using a screwdriver, turn radius-reduction screw to reduce radius up to 35%. Adjust wet or dry.

3.0 Pre-Installed Nozzle* Performance Chart

Pressure PSI	25	35	45	55
Radius ft.	29	31	31	32
Flow GPM	2.17	2.60	3.00	3.25

**Rain Curtain™
Nozzle Technology*

for even water distribution

Questions? Please call 1-800-Rain Bird
or visit us at www.rainbird.com

© 2002 Rain Bird Corporation