

## LEGEND

MAINLINE PIPE - SIZE AS SHOWN

- WATER METER PER LOCAL CODE
- BACKFLOW PREVENTION ASSEMBLY PER LOCAL CODE
- RAIN BIRD 200-EFB-CP MASTER VALVE
- RAIN BIRD FS200B FLOW SENSOR
- RAIN BIRD 5-RC QUICK COUPLING VALVE
- RAIN BIRD PEB ELECTRIC CONTROL VALVE
- ISOLATION GATE VALVE SIZE TO MATCH MAINLINE
- RAIN BIRD ESP12LXME/ESPLXMSM12 IRRIGATION CONTROLLER 24 STATIONS AVAILABLÉ, 24 STATIONS USED
- RAIN BIRD WR2 WIRELESS RAIN/FREEZE SENSOR

	RAIN BIRD F4-	PC-SS-P @ 80 PSI	
	NOZZLE	FLOW(GPM)	RADIUS(FEET)
4	4	4.6	43'
8	8	9.4	53'
14	14	16.2	61'
	RAIN BIRD F4-FC-SS-P @ 80 PSI		
	NOZZLE	FLOW(GPM)	RADIUS(FEET)
14	14	16.2	61'

—INDICATES CONTROLLER AND CONTROLLER STATION NUMBER—INDICATES LATERAL DISCHARGE IN GPM -INDICATES REMOTE CONTROL VALVE SIZE

## **GENERAL NOTES**

- 1. DESIGN IS BASED UPON A MAXIMUM FLOW OF 113 GPM AND A MINIMUM PRESSURE OF 105 PSI DOWNSTREAM OF BACKFLOW PREVENTION DEVICE. IF SUFFICIENT PRESSURE IS NOT AVAILABLE AT POINT-OF-CONNECTION A BOOSTER PUMP WILL NEED TO BE INSTALLED. CONTACT A RAIN BIRD REPRESENTATIVE FOR THE APPROPRIATE PUMP FOR THE SITE.
- 2. SPRINKLER LOCATIONS ARE TO SCALE. PIPE LOCATIONS ARE DIAGRAMMATIC.
- 3. ALL SPRINKLERS ARE TO BE INSTALLED ON RAIN BIRD TSJ-12 SWING JOINTS.
- 4. ALL VALVES ARE TO BE INSTALLED WITHIN RAIN BIRD VB SERIES VALVE BOXES.
- 5. PROVIDE RAIN BIRD #55K-1 KEY (1" MALE OUTLET) AND SH-2 SWIVEL HOSE ELL FOR EACH QUICK COUPLING VALVE.
- 6. REFER TO RAIN BIRD CATALOG AND INSTALLATION DETAILS FOR MORE DETAILED INFORMATION ABOUT EACH COMPONENT.
- 7. PIPES SHOULD NOT BE INSTALLED UNDER THE CLAY WICKET
- 8. CONSULT WITH OWNER FOR PREFERENCE REGARDING VALVE INSTALLATION WITHIN PLAYING SURFACE.

LARGE CRICKET FIELD

6504 SPRINKLER

Project:

0' 15' 30' GRAPHIC SCALE

Date: May 31, 2016

Drawing Number:

variables, Rain Bird expressly recommends the use of a qualified irrigation designer.