



Rain Bird PSRPL Rain Water Harvesting Pump Control U-220 volt

CATALOG NUMBER

RBRB241WG2

WIRING DIAGRAM

RBRB241WG2111

DATE CODE

ENCLOSURE RATING

Nema Type: 3R

PHASE

SINGLE

HERTZ

Sixty (60)

LARGEST MOTOR

5

ELECTRICAL RATING

220 v 17 FLA

SHORT CIRCUIT RATING

220 v 5kA



If you have any questions about this product, please visit: www.rainbird.com or call: 1 800-724-6247

Use copper wire rated at 75 Deg. Celcius only - - - Disconnect supplied by others.
NOTE: all motors must be thermally protected. Circuit protection must be provided by installer.
Grounding per N.E.C.- Ground lug torque: 45 in/lb. Terminal block torque specs: 9m/lb.

THIS PRINT IS THE PROPERTY OF RAINBIRD CORPORATION, AND IT EMBODIES A PROPRIETARY DESIGN WHICH SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES UNLESS SPECIFIC WRITTEN AUTHORIZATION BY RAINBIRD CORPORATION IS GIVEN. THIS PRINT IS LOANED, SUBJECT TO RETURN UPON DEMAND.