



Controller Cross-Reference Guide



ESP-TM2



RC2



ESP-ME3



ESP-2WIRE



ESP-LXME2
ESP-LXME2 PRO



ESP-LX-IVM
ESP-LX-IVM PRO



ESP-BAT-BT

	🏠 Residential		🏠/🏢 Residential/Commercial		🏢 Commercial		🔋 Battery-Operated
Stations	Fixed 4, 6, 8 or 12	Fixed 8	Modular 22	Fixed 50	Modular 48 (5 Simulstations)	Fixed 60 or 240 (8 or 16 Simulstations)	Fixed 1, 2, 4, or 6
Programs	3	3	4	4	40	10 or 40	4
Remote Management	LNK2	iQ 4.0 2.0 App	LNK2	LNK2	Requires: iQ 4.0 and/or LNK2	Requires: iQ 4.0 and/or LNK2	2.0 App
Flow Sensing	No	No	High and Low Flow Leak Detection	High and Low Flow Leak Detection	High and Low Flow Leak Detection <i>*Pro Only</i>	High and Low Flow Leak Detection	No
Automatic Weather-Based Adjustments	Requires LNK2 WiFi	Built-In	Requires LNK2 WiFi	Requires LNK2 WiFi	Requires: iQ 4.0 and/or LNK2 WiFi	Requires: iQ 4.0 and/or LNK2 WiFi	Monthly Seasonal Adjust
Features	<ul style="list-style-type: none"> • Cost Effective and Easy to Use 	<ul style="list-style-type: none"> • Seamless Mobile Pairing and Fast, Intuitive Programming 	<ul style="list-style-type: none"> • Advanced Residential Controller • 1 Master Valve • 1 Flow Sensor 	<ul style="list-style-type: none"> • 50-Station Capacity Comes Standard • Compatible with Standard Direct Burial Irrigation Wire and Wire Connectors • Decoder Auto-Address 	<ul style="list-style-type: none"> • Next-Generation Modular Control • PRO = Flow and 2nd M.V. Output for Station-Level Pump Control 	<ul style="list-style-type: none"> • Revolutionary 2-Wire Control with Smart Valve Technology • 5 or 10 Master Valves • 5 or 10 Flow Sensors 	<ul style="list-style-type: none"> • 3-5 Year Battery Life • Device Mapping • Controller Sharing with Team • Cycle+Soak™ • Offline Mode • Seconds-Based Irrigation
	Learn More	Learn More	Learn More	Learn More	Learn More	Learn More	Learn More